

Conductive Polymer Aluminum Solid Electrolytic Capacitors

Classification	Series	Configuration	Applications	Category Temperature Range (°C)	Features					Rated Voltage Range (V.D.C)	Rated Capacitance Range (µF)	Tolerance on Rated Capacitance (%)	Page
					Standard type	Low ESR	High Capacitance	Long Life	Anti-cleaning solvent				
Chip type	CF	32	Standard	-55 to +105	●				●	2.5 to 25	3.3 to 1500	±20	27
	CJ	32	Low ESR, Higher Capacitance	-55 to +105		●	●		●	2.5 to 16	33 to 2700	±20	30
	<b>NEW</b> CK	32	Ultra Low ESR	-55 to +105		●			●	2.5 to 6.3	220 to 2200	±20	32
	CG	32	Higher Capacitance	-55 to +105			●		●	2.5 to 16	47 to 3300	±20	34
	<b>NEW</b> CS	32	Long Life Assurance	-55 to +105				●	●	4 to 16	22 to 560	±20	36
Radial Lead type	LF	04	Standard	-55 to +105	●				●	2.5 to 25	6.8 to 1500	±20	38
	LE	04	Ultra Low ESR	-55 to +105		●			●	2.5 to 6.3	470 to 1500	±20	40
	LG	04	Higher Capacitance	-55 to +105			●		●	2.5 to 16	330 to 3900	±20	42
	<b>NEW</b> LS	04	Long Life Assurance	-55 to +105				●	●	2.5 to 16	100 to 1500	±20	44

Above description is a feature against AK-225AES.

**NEW** Radial Lead Type, High Voltage / Long Life LV series